



LanReady Technologies Inc.

3F., No.166, Sinhu 2nd Rd., Neihu District, Taipei City 114, Taiwan

Tel: 886-2-2796-8188 Fax: 886-2-2796-8158 <http://www.lanready.com>

Network on Demand Network on Demand Network on Demand Network on Demand Network on Demand

Model : NAS810D (Preliminary)

ver 3.0 (Date: April 8,09)

Gigabit Network 1-bays SATA Hard-Disk Storage Server



Product Feature

- Support BT Download
- Support Down Load Station Function
- UPnP AV Media server
- FTP server
- Samba Server
- 10/100/1000 Ethernet supports

Hardware Specification	
CPU	Oxford 810SE – 370MHz
Flash	4MB
RAM	128MB
Ethernet	RJ 45 (10/100/1000 Mbps) * 1
Hard Drive Interface	SATA/II x 1
USB2.0	USB Master x 1 USB Slave x 1
Buttons	Power , Copy-In
LED	HDD Access , LAN ,USB Master, USB Slave

Software Specification	
Networking Protocols	NFS (Linux Client support) SMB CIFS
File System	EXT3 FAT(external Disk only) NFS (external Disk Read only)



LanReady Technologies Inc.

3F., No.166, Sinhu 2nd Rd., NeiHu District, Taipei City 114, Taiwan

Tel: 886-2-2796-8188 Fax: 886-2-2796-8158 <http://www.lanready.com>

Network on Demand Network on Demand Network on Demand Network on Demand Network on Demand

File Sharing	Max User Accts : 2048 Max Groups : 64
Application	File Station iTunes Server BT Down Load Download Station
UPnP AV Multimedia Service Support	<ul style="list-style-type: none"> ● Sony PS3 , Microsoft Xbox 360 Audio Format : AAC,FLAC,M4A,MP3,Ogg Vorbix, WAV,WMA,WMABVR,WMA Pro,WMA Lossless Video Format : ASF,AVI,DAT,DivX ,MP4,MPEG1,MPEG2,MPEG4,VOB,WMV,XVid Image Format: BMP,JPG(jpe,jpeg), GIF,ICO,PNG,PSD,TIF(tiff),UFO Playlist Format : WPL,M3U Audio Station Video Image Playlist
iTunes Server Support	<ul style="list-style-type: none"> ● Audio Format MP3 , M4A ,M4P,WAV(4) ,AIF(4) ● Playlist Format M3U
Audio Server Support	Playlist
Photo Station Support (for ODM require only)	<ul style="list-style-type: none"> ● Video Format : ASF,AVI,MPEG1,MPEG4,WMV,XviD,Divx,FLV,DAT(2),MP4(2) MPEG(2) ,RM(2) ,RMVB(2),VOB(2) ● Image Format: BMP,JPG(jpe,jpeg)
Backup Solution	USB Copy-In
Management	Web-base Installation Management UI BT Port Range Set up E-mail Alert Message E-mail Notification for new user Firmware Upgrade FTP Passive Port Range Setup Telnet/SSH Support User Quota Web-based Download Station
Print Support (for ODM Request)	Max Printer : 1 Printing Protocols : LPR , CIFS
Support Clients	Windows 2000 Windows XP Windows Server 2003 Windows Vista Mac OS X 10.3 Mac Mini Intel

Environmental & Mechanical Characteristics



LanReady Technologies Inc.

3F., No.166, Sinhu 2nd Rd., Neihu District, Taipei City 114, Taiwan

Tel: 886-2-2796-8188 Fax: 886-2-2796-8158 <http://www.lanready.com>

Network on Demand Network on Demand Network on Demand Network on Demand Network on Demand

Operation temperature	0 °C ~ 45 °C
Storage Temperature	-20 °C ~ 70 °C
Operation Humidity	10% to 80% Non-Condensing
Storage Humidity	5% to 90% Non-Condensing
Hard Drive Interface	SATAI/II x 1
AC Input	90V to 230V
DC Output Power Voltage	12V
Power Frequency	50Hz to 60Hz Single Phase
Dimension	53(L) x 94(w) x 17.5(H) mm
Weight	Net weight: 1.2Kg Gross weight: 2.1Kg