

Model : NAS840M (Preliminary- V3)

Gigabit Network 4-bays SATA Hard-Disk Storage Server w/RAID Function



Product Feature

- Support RAID 0 , RAID 1,RAID 5
- Support ADS (Windows- Authentication)
- Support Download Station
- Support BT Download
- Media server
- FTP server
- Samba Server
- Print Server
- 10/100/1000 Ethernet supports

Hardware Specification	
CPU	500MHz
Flash	8MB
RAM	128MB
Ethernet	RJ 45 (10/100/1000 Mbps) * 1
Hard Drive Interface	SATA/II x 4
USB2.0	2

Software Specification	
Networking Protocols	NFS (Linux Client support) SMB CIFS
Domain Integration	ADS (Windows- Authentication) Domain User login via Samba/FTP
File System	EXT3



LanReady Technologies Inc.

3F., No.166, Sinhu 2nd Rd., Neihsu District, Taipei City 114, Taiwan

Tel: 886-2-2796-8188 Fax: 886-2-2796-8158 <http://www.lanready.com>

Network on Demand Network on Demand Network on Demand Network on Demand Network on Demand

	FAT(external Disk only) NFS (external Disk Read only)
File Sharing	Max User Accts : 2048 Max Groups : 64
Application	File Station iTunes Server Download Station
UPnP AV Multimedia Service Support	<ul style="list-style-type: none"> ● Sony PS3 , Microsoft Xbox 360 Audio Format : AAC,FLAC,M4A,MP3,Ogg Vorbix, WAV,WMA,WMABVR,WMA Pro,WMA Lossless Video Format : ASF,AVI,DAT,DivX ,MP4,MPEG1,MPEG2,MPEG4,VOB,WMV,XVid Image Format: BMP,JPG(jpe,jpeg), GIF,ICO,PNG,PSD,TIF(tiff),UFO Playlist Format : WPL,M3U <ul style="list-style-type: none"> ● Audio Station ● Video ● Image ● Playlist
iTunes Server Support	<ul style="list-style-type: none"> ● Audio Format MP3 , M4A ,M4P,WAV(4) ,AIF(4) ● Playlist Format M3U
Audio Server Support	Playlist
Photo Station Support (for ODM require only)	<ul style="list-style-type: none"> ● Video Format : ASF,AVI,MPEG1,MPEG4,WMV,XviD,Divx,FLV,DAT(2),MP4(2) MPEG(2) ,RM(2) ,RMVB(2),VOB(2) ● Image Format: BMP,JPG(jpe,jpeg)
Backup Solution	USB Copy-In
Management	Web-base Installation Management UI BT Port Range Set up E-mail Alert Message E-mail Notification for new user Firmware Upgrade FTP Passive Port Range Setup Telnet/SSH Support User Quota Web-based Download Station
Print Support (for ODM Request)	Max Printer : 1 Printing Protocols : LPR , CIFS
Support Clients	Windows 2000 Windows XP Windows Server 2003 Windows Vista Mac OS X 10.3 Mac Mini Intel



LanReady Technologies Inc.

3F., No.166, Sinhu 2nd Rd., Neihu District, Taipei City 114, Taiwan

Tel: 886-2-2796-8188 Fax: 886-2-2796-8158 <http://www.lanready.com>

Network on Demand Network on Demand Network on Demand Network on Demand Network on Demand

Environmental & Mechanical Characteristics	
Operation temperature	0 °C ~ 45 °C
Storage Temperature	-20 °C ~ 70 °C
Operation Humidity	10% to 80% Non-Condensing
Storage Humidity	5% to 90% Non-Condensing
Hard Drive Interface	SATAI/II x 4
AC Input	90V to 230V
DC Output Power Voltage	12V
Power Frequency	50Hz to 60Hz Single Phase